



High reading accuracy
Fast & Efficient data capture
Cutting-edge OCR technology
Customized client requirements

AL100 PASSPORT READER

INTRODUCTION

AL100 Passport Reader for international passport is ultra fast Passport Reader with High-precision OCR algorithm consists of a unique hardware device and cutting-edge OCR engine. Ideally and accurately Capture data with e-passports, Visas and other travel documents from different countries. This multi-functional Reader also supports Auto-sensing trigger that can be easily operated and a simple API/SDK provided can be easily integrated.

FEATURES

- Compliance with ICAO Doc 9303 specifications
- A variety of travel documents recognized (by award-winning OCR engine)
- Easily control: automatically trigger
- 3.0 Megapixel provided, and the resolution of image captured is 390dpi
- Provided imaging in Visible image, Infrared (IR) image, and Ultraviolet (UV) image
- Customized FULL-PAGE contents extraction with different travel documents

SPECIFICATIONS

Readable documents (Need to comply with ICAO Document 9303 specifications)	Passport (Types)	e-Passport (Optional) <ul style="list-style-type: none"> • contactless integrated circuit (CIC) reading and writing • Supporting ISO 14443 Type A/B • Supporting e-Passports Basic Access Control (BAC) • Supporting Active/Passive authentications of e-Passport
	Others (Customized)	(Other travel documents) Full page processing
Data captured & Processing time (Seconds)	e-Passport	Reading time depends on user's RFID tag, Operating system and types of chip
	Others	Less than 1s (just OCR processing)
Imaging	Window size	127mm×96mm Resolution: 390 dpi
	Sensor	CMOS, 3 Megapixels (2048*1536)
	Resolution	390 dpi
	Illuminations	Visible, IR, UV imaging (Optional)
Software Development Kit Features	Including DLLs, OCXs, Demonstrations, Samples (support for VC, VB, C #, Java)	
Trigger	Auto-trigger	
Indicator	4 status indicator LEDs (for Power, Ready, Error, and Warning) 4 user definable buttons	
External interface	USB 2.0 Integrated USB 2.0 Hub for external peripherals	
Power Requirements	AC Input	100~240V, 50-60Hz 0.8A
	DC Output	12V, 2A
Environmental	Operating temperature	-10°C to 50°C operating; -20°C to 50°C storage
	Operating humidity	20% to 95%(non-condensing)
Dimensions	Length	248mm
	Width	216mm
	Height	152mm
	Weight	1.5kg, (but the Weight with package is 2.7kg)

APPLICATION

Embassies

Border crossings

Public securities

- Exit and Entry Management Bureau
- Frontier Inspection station
- Local police station

Airports, Train/ Bus Terminals

Hotels, Banks, and Travel agencies



ALL ID ASIA PTE LTD

67, Ayer Rajah Crescent, #02-18
Ayer Rajah Industrial Estate,
Singapore 139950
Tel : +65 6778 0075
Email : enquiry@allid.com.sg
Web : www.allid.com.sg

ALL ID ASIA SDN BHD

A-1-36, IOI Boulevard, Jalan Kenari 5,
Bandar Puchong Jaya, 47100
Puchong Jaya, Selangor, Malaysia
Tel : +603 8075 1888
Email : enquiry@allid.com.my
Web : www.allid.com.my

PT. ALL ID INDONESIA

Ruko Mutiara Taman Palem C9-33,
Jalan Kamal Raya Outer Ring Road,
Cengkareng, Jakarta Barat, Indonesia
Tel : +62 (21) 29020190
Email : enquiry@allid.co.id
Web : www.allid.co.id

ALL ID MYANMAR

MICT PARK, Block 3, First Floor, B - 31,
Hlaing University Campus Road,
Hlaing Township, Yangon, Myanmar
Tel : (+951) 652265, 652302, 652303
Email : marketing@allid.com.mm
Web : www.allid.com.mm