

ALL ID BT323

Bluetooth 2D Barcode Scanner

Features

1. Wireless scanning of 1D & 2D barcodes with Bluetooth
2. Scanning speed is more than 300 scans per second
3. Fast and easy to scan from paper, print and screen
4. Easy to connect to various devices with one key only
5. Designed to withstand 1.5m drops
6. Large capacity battery allows more than 8 hours of continuous scanning and 7 days of standby



Specifications

Scan Performance:

- **Scan Mode:** Automatic / handheld
- **Alarm Mode:** LED light alarm, Buzzer alarm
- **Read speed:** 300scan/sec
- **Resolution:** 640(horizontal) x 480(vertical), 256 gray levels
- **Scan Angle:** 45°(horizontal);30°(vertical)
- **Scan depth of field:** 5 mil(Code 39) 30~120mm
13 mil(UPC/EAN) 30~305mm
20 mil(Code 39) 30~450mm
10mil(QR code) 40~225mm
- **Revolve Angle:** Roll : 0-360°、 Pitch : ±60°or greater、 Yaw : ±55°or greater
- **Barcode Type:** Australian Post, Aztec, BPO, Canada Post, Codabar, Codablock, Code 11, Code 39, Code 93, Code 128/EAN128, DataMatrix, Dutch Post, EAN.UCC Composite, Interleaved 2 of 5, Japan Post, Matrix 2 of 5, MaxiCode, MicroPDF417, MSI Code, PDF417, Planet, Plessey Code, Postnet, QR code, RSS, Standard 2 of 5, Telepen, TLC 39, UPC/EAN,ETC.

Electrical:

- **Voltage:** DC 5V ± 5%
- **Battery Capacity:** 1600mA
- **Interfaces:** Bluetooth V3.0/433MHz(optional) Bluetooth 30m, 433M 100m(in vacant space)
- **Light:** Visible Red light 630+10nm
- **Light Level:** Can resistive the Interference of lamp-light and sun-shiningty
- **ESD protect:** 15KV
- **Electric Safety:** En55022: 2006 + A1: 2007
En55024: 1998 + A1: 2001 + A2: 2003

Environmental:

- **Operating Temperatures:** -20 ° C ~ 60 ° C
- **Storage Temperatures:** 30 ° C ~ 70 ° C
- **Humidity:** 5% ~ 95% RH
- **Drop:** Designed to withstand 1.5m drops

Environmental:

- **Dimensions (LxWxH):** 150mm x 70mm x 95mm
- **Weight:** <155g (not include cable)
- **Color:** Black
- **Material:** ABS + EVA

Product features, specifications and appearances are subject to change without notice.
Copyright © 2018 All rights reserved. This product is manufactured, distributed, and sold by All ID Asia.



Singapore (HQ)
All ID Asia Pte Ltd
+65-6778-0075
enquiry@allid.com.sg
www.allid.com.sg

Malaysia
All ID Asia Sdn Bhd
+603-8075-1888
enquiry@allid.com.my
www.allid.com.my

Indonesia
PT All ID Indonesia
+62 21-4517-330
enquiry@allid.co.id
www.allid.co.id

Myanmar
All ID Myanmar
+951-652265
enquiry@allid.com.mm
www.allid.com.mm

Sri Lanka
All ID Sri Lanka
+65-6778-0075
enquiry@allid.com.lk
www.allid.com.lk